



RECOMMENDED LAYOUT
FOR .062 THICK P.C. BOARD

- PARTS COMPLY WITH TE SOLDERABILITY SPEC. NO. 109-11-3
- CONTACT IS PLATED OVERALL WITH .000050 NICKEL, THEN .000030 GOLD OVER CONTACT LENGTH INDICATED AND TIN PLATED ON SOLDER TAIL END.
- DIMENSION SHOWN REPRESENT PRODUCT IN DRY CONDITION. ADDITIONAL 2% GROWTH DUE TO END USE LOCATION MOISTURE ABSORPTION MAY OCCUR AND SHOULD BE ACCOUNTED FOR.

SUPERSEDED BY
2-1586546-0

1-380999-0	NYLON	NATURAL	COPPER ALLOY GOLD
1-380999-0	NYLON	NATURAL	COPPER ALLOY PRE-TIN
ASSEMBLY NO.	HSG. MATL.	COLOR	PIN MATL. FINISH

REVISION RECORD				NUMBER		DWG. SIZE		NUMBER		NAME		REMARKS		ITEM NO.	
U4	REVISED PER ECR-21-117185	PJ	VS	2007	1	13	10	1	1	1	1	1	1	1	1
U3	REVISED PER ECR-18-008156	JB	DZ	2018	1	13	10	1	1	1	1	1	1	1	
U2	REVISED PER ECR-13-008342	AV	RP	12	NOV	13	1	1	1	1	1	1	1	1	
U1	REVISED PER ECO-11-005294	RK	HMR	12	APR	11	1	1	1	1	1	1	1	1	
LTR	REVISION RECORD	DR	CHK	D/JE											

REQUIRED PER ASSEMBLY		MATERIAL AND FINISH		TYPE		NAME		REMARKS		ITEM NO.	
DR	3/20/13	SEE TABLE									
CHK	3/20/13										
DE	4-3-73										
APP	4-3-73										

WIRE - RANGE - INSULATION		TOLERANCE EXCEPT AS NOTED		SCALE		LOC		NO		P	

NAME		CIRCUIT		MATE-N-LOK		P.C. BOARD HEADER	